



## ASTARIGLAS® GP CAST ACRYLIC – COLOURS

**ASTARIGLAS® GP Cast Acrylic** Sheet is a premium material made from 100% virgin MMA (Methyl Methacrylate) for outstanding clarity, strength, and weather resistance. Lighter and stronger than glass, it offers excellent rigidity, surface hardness, and optical quality. Easy to cut, drill, form, machine, and polish, it's ideal for both indoor and outdoor use. Resistant to most chemicals and temperature fluctuations from -40°C to +80°C, it maintains clarity and durability over time, making it perfect for signage, displays, glazing, and decorative applications.

### KEY FEATURES

- Better impact strength than glass
- Lightweight
- Easily fabricated, thermoformed or polished
- Optical clarity
- High light transmission (clear colour)
- Chemical resistance to common acids
- Excellent weatherability & UV resistance

### PRODUCT APPLICATIONS

- Exterior & interior signage
- POS displays
- Glazing & protective screens
- Display cabinets
- Brochure holders
- Marine windscreens
- Industrial, joinery & automotive parts

### PROPERTIES

GENERAL		RESULTS
Weight (3mm)		3.57kg/m <sup>2</sup>
Relative Density (ISO 1183)		1.19g/cm <sup>3</sup>
Gauge Tolerance (ASTARI TDS)		+/- 0.4mm
Light Transmission (Clear colour)		92%
Cleaning:	Warm soapy water & soft cloth	
MECHANICAL		
Tensile Strength (ISO 527)		70Mpa
Flexural Strength (ISO 178)		116Mpa
THERMAL		
Service Temperature		80°C
Vicat Softening Temp (ISO 306A)		>110°C
Co-Efficient (ASTM D696)		x 10 <sup>-5</sup> .K <sup>-1</sup>
Flammability (AS/NZS 3837:1)		Group 4

### PRODUCT RANGE

COLOUR	GAUGE	SIZE
White 402	2-20mm	2440x1220mm
	3mm 4.5mm	3050x2050mm
White 401	4.5mm	2440x1220mm 3050x2050mm
	3-25mm	2440x1220mm
Black	3-6mm	3050x2050mm
	3-25mm	2440x1220mm
Fluro	3mm	2440x1220mm
Colours	3-10mm	2440x1220mm
	4.5mm	3050x2050mm
Cut to size available upon request		

### COLOURS



Coloured swatch may not represent physical product.

