



VIPET® PETG

Vipet® PETG is a premium co-polyester sheet formulated to achieve exceptional clarity, durability and fabrication ease for high-quality signage, displays and packaging. With its superior impact strength compared to Acrylic and no requirement for pre-drying prior to vacuum forming, **Vipet® PETG** offers designers and fabricators limitless freedom and efficiency. It is also suitable for direct contact with food, making it ideal for packaging, display cases, protective covers, dispensers and more. **Vipet® PETG**'s chemical resistance, hygienic surface and easy to clean properties ensure safety and compliance with food-grade standards.

KEY FEATURES

- Crystal-clear appearance
- High impact resistance
- Exceptional thermoforming capabilities
- Food-safe surface
- Easy to cut, route, print & bond
- Chemical resistant
- Moisture resistant

PRODUCT APPLICATIONS

- Medical & food packaging
- Industry guards & covers
- Vending machine components
- Product dispensers
- POS displays
- Signage

COLOURS



Coloured swatch may not represent physical product.

PROPERTIES

GENERAL		RESULTS
Weight		2.2kg/m ²
Density (ISO 1183-1)		1.1g/cm ³
Water Absorption (ISO 62)		0.3%
Cleaning: Warm soapy water & soft cloth		
MECHANICAL		
Tensile Strength (ISO 527-2)		50Mpa
Flexural Strength (ISO 178:2019)		2050Mpa
THERMAL		
Vicat Softening Temperature (ISO 306:2013)		79°C
Continuous Service Temperature		55°C
Short Term Service Max Temp		65°C

PRODUCT RANGE

COLOUR	GAUGE	SIZE
Clear	0.5mm 0.75mm 1mm 1.5mm 2mm 3mm 4.5mm	2440x1220mm

